



2207 – 91 Avenue, Edmonton, AB, T6P 1L1

Ph. 780-464-5177 / 1-800-661-1092

Fx. 780-467-6516

www.behrendsbronze.com

info@behrendsbronze.com

INSTALLATION OF PLAQUES

BLIND MOUNTING

A brown paper template is included with this plaque and is to be used for drilling the mounting holes. Tape this template in the desired location for the plaque and drill through the marked holes with a drill of the same diameter as the four mounting studs, usually 3/16"

Screw the mounting studs into the four tapped holes on the back of the plaque and snug up with a pair of pliers. **DO NOT OVER-TIGHTEN**, as this may create a bump on the face of the plaque.

Align the studs with the drilled holes and push the plaque into place. Use a rubber mallet and a wad of cloth to protect the face of the plaque if extra force is required. For extra security apply a mastic type of glue on the studs, such as PL200.

Wipe clean with a soft dry cloth.

SCREWS THROUGH FACE WITH OR WITHOUT ROSETTES

Hold the plaque up to the wall in the appropriate place and mark the wall through the four drilled holes. Drill holes with appropriate size drill for the screws, or for the plastic wall plugs if mounting on drywall. Screw plaque onto surface with supplied screws. If decorative rosettes have been supplied with this plaque, glue these over top of the screws.

CAUTION – this plaque has a clear protective coating to prevent oxidizing of the surface. The coating can be easily damaged through mishandling. If cleaning is required wipe with a clean soft cloth only in the direction of the grain of the plaque, or a solution of water and mild detergent may be used. Do not use any chemical based or abrasive cleaners.